



FALA[®]
Sauberkeit für Profis

Toplan ultra

Ultrawetting maintenance cleaner

Packaging	Art.-No.	per Box	per Palett
1 l PE-bottle	2531	10	360
10 l PE-canister	2530	-	60

Properties:

Toplan ultra is an ultrawetting maintenance cleaner, who is suitable for cleaning all types of waterproof surfaces. According to CLP-regulation it is not labeled as hazardous. Processing is possible manually or by using an automatic cleaning machine. Due to its excellent wetting properties, it can also be used on difficult, water-repellent surfaces. Toplan ultra is powerful, has a high dirt-carrying capacity and is characterized by a fresh, fruity fragrance.

Field of Application:

For cleaning of all types of waterproof surfaces (rubber floors, PVC, floor polish on Linoleum, of plastic floors, glazed and unglazed porcelain stoneware tiles, natural and artificial stones etc.).

Application:

Manual processing: Use cleaning solution with a mop or cloth on the surface. The machine processing takes place by means of cleaning machines.

Dosage:


Maintenance cleaning: 20 – 40 ml to 8 l water. Intensive cleaning: 80 ml to 8 l water. Automatic cleaning: 40 ml to 10 l water.

Ingredients:

<5% nonionic surfactants, <5% anionic surfactants, perfumes, Benzyl Salicylate, Linalool, Citronellol, Hexyl Cinnamal, Limonene, Benzisothiazolinone, Methylisothiazolinone.

Productcode: GU 40

This product is intended for commercial use only. Safety data sheet available on request or at www.fala.de. For safety instructions pay attention to product label or safety data sheet.



toplan ultra / EN / 2.1

The information contained herein corresponds at the time of publication to our best present-day knowledge. It is the responsibility of the user to ensure that the product is suitable for the intended application.



For manual application
in wiping process




For manual application
on all waterproof
surfaces



No second wiping,
dries streak free



Maintenance cleaning:
Dilution of
1:400–1:200



Intensive cleaning:
Dilution of
1:100



Automatic cleaning:
Dilution of
1:250

FALA-Werk Chemische Fabrik GmbH · Stahlstraße 5 · 30916 Isernhagen · GERMANY
Tel. +49 511 97386-0 · Fax +49 511 97386-40 · info@fala.de · www.fala.de

