



# Falamat ultra

Low-foaming intensive cleaning agent suitable for automatic cleaning units, without label for hazardous goods

Packaging	Art.-No.	per Box	per Palett
10 l PE-Canister	9380	-	60

#### Properties:

Falamat ultra is an effective, quick-acting and alkaline grease and dirt remover intended for use in automatic cleaning units (automatic scrubber or brushing barrel unit) for maintenance, intermediate and intensive cleaning. Falamat ultra is characterised by a pleasant scent during application. Cleanses all kinds of waterproof floorings such as PVC, linoleum, rubber studs, natural and cast stone. Equally suitable for delicate floorings such as e.g. epoxy resin floors. Not suitable for care films of wax or acrylate. Dries up clear and streak-free. Suitable for manual wet wiping method as well.

#### Field of Application:

For use in automatic cleaning units (automatic scrubber or brushing barrel unit). Maintenance or intensive cleaning of all waterproof and alkali-resistant floorings. Heel and abrasion marks can be removed easily with a 1:1 dilution (test material compatibility beforehand).

#### Application:

For daily maintenance cleaning, fill up automatic cleaning unit with diluted cleaning agent and wipe surfaces. Manual processing: Wipe in two-step cleaning procedure. Intensive cleaning: Apply concentrated cleaning agent to flooring, allow to work (5-10 min.), scrub and remove dirty solution, rinse with clear water.

#### Dosage:

Automatic unit cleaning: 25 - 100 ml to 10 l water (dilution 1:100 - 1:400).  
Intensive cleaning: 1 l to 10 l water (dilution 1:10).


#### Ingredients:

< 5% nonionic surfactants, fragrances.

#### Productcode: GU 50

This product is intended for commercial use only. Safety data sheet available on request or at [www.fala.de](http://www.fala.de). For safety instructions pay attention to product label or safety data sheet.


The information contained herein corresponds at the time of publication to our best present-day knowledge. It is the responsibility of the user to ensure that the product is suitable for the intended application.



Machine processing using automatic cleaning unit



Manual processing in wiping procedure



Automatic cleaning unit:  
Dilution 1:100 to 1:400



Intensive cleaning:  
Dilution 1:10